



Integrated Management System

Doc. No: EYS-TO-11

First Publishing Date:
26.06.2014

Rev. Date:-

Rev No: 00

Page No: 1/2

TECHNICAL SPECIFICATION of **3x70+35+16** (XLPE)

TECHNICAL SPECIFICATIONS	UNIT	3x70+35+16 (XLPE)
Standart Use		EN 60228, Man. Spec.
PHASE CONDUCTOR		
Material		1370 EC Aluminium
Number of Al Wires		7
Compacted Diameter	mm	9,3-10,2
Insulation Thickness	mm	1,4
Overall diameter of finished cable	mm	12,1-13,0
Unit Weight of Al (compacted)	kg/km	190
Unit Weight of Insulation	kg/km	44
Overall Weight per Km of Cable	kg/km	234
Insulation Material		XLPE
Max. DC Resistance at 20°C	Ohms/km	0,443
MESSENGER		
Material		AAAC 6101
Number of Al Alloy Wires		7
Compacted Diameter	mm	6,6-7,5
Insulation Thickness	mm	1
Overall diameter of finished cable	mm	8,6-9,5
Unit Weight of Al alloy (compacted)	kg/km	95
Unit Weight of Insulation	kg/km	22,5
Overall Weight per Km of Cable	kg/km	117,5
Insulation Material		XLPE
PUBLIC LIGHTING		
Material		1370 EC Aluminium
Number of Al Wires		1
Diameter of Wire	mm	4,5
Insulation Thickness	mm	1
Overall diameter of finished cable	mm	6,5
Unit Weight of Al	kg/km	43
Unit Weight of Insulation	kg/km	15,9
Overall Weight per Km of Cable	kg/km	58,9
Insulation Material		XLPE

Rated Strength	N	1900
Max. DC Resistance at 20°C	Ohms/km	1,91
Reel Type		Non Returnable Wooden
Total Unit Weight	Kg/km	887

Identification: Colored three straight stripes with 120 degree will be applied to the phase conductors

1st phase: red

2nd phase: blue

3rd phase: white

Prepared By	Approved By
Hicran TECER Quality Assurance Manager	Kenan ÖZDEMİR Deputy General Manager